according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SANET EXTREME
UFI : E418-40QH-Q003-Q2G1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH

Rheinallee 96 55120 Mainz

Telephone : +49613196403 Telefax : +4961319642414

E-mail address : Produktsicherheit@werner-mertz.com

Responsible/issuing person

Contact person : Product development / product safety

1.4 Emergency telephone number

112

Centru za kontrolu otrovanja u Zagrebu na tel. (01) 2348 342

+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to metals, Category 1 H290: May be corrosive to metals.

Skin corrosion, Category 1 H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Hazard statements H290 May be corrosive to metals.

> H314 Causes severe skin burns and eye damage.

P102 Precautionary statements Keep out of reach of children.

Prevention:

Wear protective gloves/ protective clothing/ eye P280

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce

vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/ doctor.

Disposal:

Dispose of container into the collection of P501

recyclables only when it is completely empty.

Hazardous components which must be listed on the label:

methanesulphonic acid I-(+)-lactic acid Alcohols, C12-14, ethoxylated (7 EO)

Safety data sheet available on request.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
methanesulphonic acid	75-75-2	Skin Corr. 1B; H314	>= 5 - < 10
	200-898-6	Met. Corr. 1; H290	
	607-145-00-4	Acute Tox. 4; H302	
	01-2119491166-34	Acute Tox. 4; H312	
		STOT SE 3; H335	
		Eye Dam. 1; H318	
		specific concentration	
		Skin Corr. 1B; H314	
		5 - 100 %	
		Eye Dam. 1; H318	
		3 - < 5 %	
		Skin Irrit. 2; H315	
		3 - < 5 %	
		Eye Irrit. 2; H319	
		1 - < 3 %	
		Skin Irrit. 2; H315	

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

		1 - < 3 %	
I-(+)-lactic acid	79-33-4 201-196-2 01-2119474164-39	Skin Corr. 1C; H314 Eye Dam. 1; H318 specific concentration limit Skin Irrit. 2; H315 3 - < 5 % Eye Dam. 1; H318 >= 3 % Eye Irrit. 2; H319 1 - < 3 % Skin Corr. 1C; H314 >= 5 %	>= 3 - < 5
Alcohols, C12-14, ethoxylated (7 EO)	68439-50-9 500-213-3	Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Chronic 3; H412 M-Factor (Acute aquatic toxicity): 1 specific concentration limit Eye Dam. 1; H318 > 10 % Eye Irrit. 2; H319 > 1 - 10 %	>= 1 - < 2,5

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from

corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue

damage and blindness. Protect unharmed eye.

Continue rinsing eyes during transport to hospital.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons

Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for :

firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must

not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.

Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application

area.

To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire :

and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas

and containers

Store in upright position only. Store in original container. Store at room temperature in the original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent

leakage.

Further information on storage

stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber

category III according to EN 374.

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special workplace

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

Remove and wash contaminated clothing before re-use.

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : red

Odour : odourized

Odour Threshold : No data available pH : ca. 0,4, 100 %

at 20 °C

Melting point/range : No data available Boiling point/boiling range No data available Flash point does not flash Evaporation rate No data available Flammability (solid, gas) No data available Flammability (liquids) No data available No data available Burning rate Lower explosion limit No data available Upper explosion limit No data available Vapour pressure No data available Relative vapour density No data available Relative density : No data available Density : 1,039 g/cm3 at 20 °C



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Water solubility : completely soluble

Solubility in other solvents : No data available

Partition coefficient: n- : No data available

octanol/water

Ignition temperature : No data available
Thermal decomposition : No data available
Viscosity, dynamic : 1 mPa.s at 20 °C

Viscosity, kinematic : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.

Our company does not place any orders for animal testing for the finished product or the ingredients. However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Product:

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

methanesulphonic acid

75-75-2:

Acute oral toxicity : LD50 (Rat): 200 mg/kg

LD50 (Rat): 649 mg/kg

Acute inhalation toxicity : LC0 (Mouse): > 1,88 mg/l

Exposure time: 1 h

LC0 (Rat): 0,74 mg/l Exposure time: 6 h

Acute dermal toxicity : LD50 (Rabbit): > 1.000 - 2.000 mg/kg

I-(+)-lactic acid

79-33-4:

Acute oral toxicity : LD50 (Rat): 3.730 mg/kg

LD50 (Mouse): 4.875 mg/kg

LD50 Oral (Guinea pig): 1.810 mg/kg

Acute inhalation toxicity : LC50 (Rat): 7,94 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Alcohols, C12-14, ethoxylated (7 EO)

68439-50-9:

Acute oral toxicity : LD50 Oral (Rat): 300 - 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Germ cell mutagenicity

Germ cell mutagenicity : Not Rated

Components:

Alcohols, C12-14, ethoxylated (7 EO)

68439-50-9:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT - single exposure : The substance or mixture is not classified as specific target organ

toxicant, single exposure.

STOT - repeated exposure : The substance or mixture is not classified as specific target organ

toxicant, repeated exposure.

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

methanesulphonic acid

75-75-2:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 - 100 mg/l

Exposure time: 96 h
Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 10 - 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Method. OEGD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 10 - 100

mg/l

Exposure time: 72 h

Test Type: Growth inhibition

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 10 - 100 mg/l

Exposure time: 72 h

Method: see user defined free text Remarks: see user defined free text

I-(+)-lactic acid

79-33-4:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l

Exposure time: 96 h

LC50 (Fish): 320 mg/l Exposure time: 48 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 130 mg/l

Exposure time: 48 h

EC50 (Daphnia pulex (Water flea)): 240 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum): 3.500 mg/l

ErC50 (Pseudokirchneriella subcapitata (microalgae)): 2.800 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 :> 100 mg/l

Exposure time: 3 h

Alcohols, C12-14, ethoxylated (7 EO), Alcohols, C12-14. ethoxylated

68439-50-9:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 1 - 10 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: OECD Test Guideline 203

LC50 (Fish): > 1 mg/l Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 1 - 10 mg/l

Exposure time: 72 h

Test Type: static test

Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 0,1 - 1 mg/l

Exposure time: 72 h Test Type: static test

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Bacteria): 140 mg/l

Toxicity to soil dwelling : 220 mg/kg

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

organisms Species: Eisenia fetida (earthworms)

Plant toxicity : 10 mg/l

Species: Lepidium sativum (cress) Method: see user defined free text

12.2 Persistence and degradability

Components:

methanesulphonic acid

75-75-2:

Biodegradability : Result: rapidly biodegradable

Biodegradation: > 99 % Exposure time: 28 d

I-(+)-lactic acid

79-33-4:

Biodegradability : Result: rapidly biodegradable

Biochemical Oxygen Demand

(BOD)

450 mg/g

Incubation time: 5 d

600 mg/g

Incubation time: 20 d

Chemical Oxygen Demand

(COD)

900 mg/g

ThOD : 1.067 mg/g

Alcohols, C12-14, ethoxylated (7 EO), Alcohols, C12-14. ethoxylated

68439-50-9:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d Method: OECD 301 A

Result: rapidly biodegradable Biodegradation: > 60 % Exposure time: 28 d Method: OECD 301 B

12.3 Bioaccumulative potential

Components:

methanesulphonic acid

75-75-2:

Partition coefficient: n-

: log Pow: -2,38

octanol/water

12.4 Mobility in soil

Components:

methanesulphonic acid

75-75-2:

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Distribution among : Koc: 1

environmental compartments Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemical or

used container.

In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : 3265 IMDG : 3265 IATA : 3265

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(methanesulphonic acid)

IMDG : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(methanesulphonic acid)

IATA : Corrosive liquid, acidic, organic, n.o.s.

14.3 Transport hazard class(es)

ADR : 8 IMDG : 8 IATA : 8

14.4 Packing group

ADR

Classification Code : C3
Packaging group : III
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Packaging group Ш Labels 8

EmS Number F-A, S-B

IATA

(Cargo) Corrosive liquid, acidic, organic, n.o.s. (Passenger) Corrosive liquid, acidic, organic, n.o.s.

Packaging group : III 8

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant no

IATA Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and : Not applicable

the Council concerning the export and import of dangerous

chemicals

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles (Annex XVII)

See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

TA Luft List (Germany)

Total dust: Not applicable

Inorganic substances in powdered form: Not applicable

Inorganic substances in vapour or gaseous form: Not applicable

Organic Substances: : portionClass 1: 7 % Carcinogenic substances: Not applicable

Mutagenic: Not applicable

Toxic to reproduction: Not applicable

Volatile organic compounds

(VOC) content

Directive 2010/75/EU of 24 November 2010 on industrial emissions

(integrated pollution prevention and control)

Update: Percent volatile: 7 %

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

according to Detergents Regulation EC 648/2004 : <5% Non-ionic surfactants, Perfumes

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H290 : May be corrosive to metals. H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Met. Corr. : Corrosive to metals Skin Corr. : Skin corrosion

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

according to Regulation (EC) No. 1907/2006



SANET EXTREME

WM 0716544 Order number: 0716544

Version 1.3 Revision Date 12.01.2024 Print Date 22.03.2024

Classification of the mixture: Classification procedure:

Met. Corr. 1 H290 Calculation method

Skin Corr. 1 H314 Based on product data or assessment Eye Dam. 1 H318 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000006049